

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS
2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous
Products Regulation (HPR)

Revision Date 08-May-2025

Revision Number 1

1. Identification

Product identifier

Product Name CND SHELLAC Topcoat

Other means of identification

Product Code(s) 470267, 467292, 4700637

UN-No UN1263

Bulk Number 4702670001, 4701934001, 4700637001

Brand CND

Category Nail

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use No information available

Restrictions on use No information available

Details of the supplier of the safety data sheet

Initial supplier identifier

Revlon Research Center

Supplier Address

2121 Route 27 Edison, NJ 08818

Emergency telephone number

Emergency Telephone Number INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. Hazard(s) identification

Classification

Flammable liquids	Category 2
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3

Label elements



Danger**Hazard statements**

Highly flammable liquid and vapor

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

May cause drowsiness or dizziness

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust, fume, gas, mist, vapors and spray

Contaminated work clothing must not be allowed out of the workplace

Use only outdoors or in a well-ventilated area

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground and bond container and receiving equipment

Use explosion-proof electrical, ventilating, lighting and .? equipment

Use only non-sparking tools

Take action to prevent static discharges

Wear protective gloves, eye protection and face protection

Keep cool

Precautionary Statements - Response

Specific treatment (see .? on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice and attention

Skin

If skin irritation or rash occurs: Get medical advice and attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water and then shower

Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

Fire

In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Precautionary Statements - Disposal

Dispose of contents and container to an approved waste disposal plant

Other information

May cause long lasting harmful effects to aquatic life.

3. Composition/information on ingredients**Substance**

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Ethyl acetate 141-78-6 (<20)	141-78-6	<20	-	-
Isobornyl Methacrylate 7534-94-3 (<20)	7534-94-3	<20	-	-
Butyl Acetate	123-86-4	<10	-	-

123-86-4 (<10)				
Ethyl Trimethylbenzoyl Phenylphosphinate 84434-11-7 (<5)	84434-11-7	<5	-	-
Bis-Trimethylbenzoyl Phenylphosphine Oxide 162881-26-7 (<1)	162881-26-7	<1	-	-

4. First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms	Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
Effects of Exposure	No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians	May cause sensitization in susceptible persons. Treat symptomatically.
---------------------------	--

5. Fire-fighting measures

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by skin contact.
Explosion Data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures****Personal precautions**

Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other information

Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up**Methods for containment**

Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up

Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. Handling and storage**Precautions for safe handling****Advice on safe handling**

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

8. Exposure controls/personal protection**Control parameters****Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
---------------	-----------	----------	-------

ETHYL ACETATE	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m ³
Butyl Acetate	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³

Chemical name	Alberta	British Columbia	Ontario	Quebec
ETHYL ACETATE	TWA: 400 ppm TWA: 1440 mg/m ³	TWA: 150 ppm	TWA: 400 ppm	TWA: 400 ppm TWA: 1440 mg/m ³
Butyl Acetate	TWA: 150 ppm TWA: 713 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³	TWA: 50 ppm STEL: 150 ppm	TWA: 50 ppm STEL: 150 ppm	TWA: 50 ppm STEL: 150 ppm

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
Ethyl acetate 141-78-6 (<20)	TWA: 400 ppm	TWA: 400 ppm	TWA: 400 ppm	TWA: 400 ppm
Butyl Acetate 123-86-4 (<10)	TWA: 50 ppm STEL: 150 ppm	TWA: 50 ppm STEL: 150 ppm	TWA: 50 ppm STEL: 150 ppm	TWA: 50 ppm STEL: 150 ppm

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
Ethyl acetate 141-78-6 (<20)	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm TWA: 1400 mg/m ³ STEL: 400 ppm STEL: 1400 mg/m ³
Butyl Acetate 123-86-4 (<10)	TWA: 150 ppm STEL: 200 ppm	TWA: 50 ppm STEL: 150 ppm	TWA: 150 ppm STEL: 200 ppm	TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³

Appropriate engineering controls**Engineering controls**

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Tight sealing safety goggles.

Hand protection

Wear suitable gloves. Impervious gloves.

Skin and body protection

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.
Antistatic boots.

Respiratory protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.
---------------------------------------	--

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Viscous
Color	Slightly Blue transparent
Odor	Mild Ester like
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	100 °C / 212.0 °F	None known
Flash Point	-4 °C / 24.8 °F	CC (closed cup)
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	No information available
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	1.03-1.06	None known
Water solubility	Insoluble in water	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other information

Explosive properties	No information available
Oxidizing properties	No information available
Softening Point	No information available
Molecular Weight	No information available
VOC content	25.65%
Liquid Density	No information available
Bulk Density	No information available

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under ambient conditions when stored properly (See Section 7, Storage and Handling).
Possibility of hazardous reactions	None under normal processing.
Hazardous Polymerization	May occur, if exposed to extremely high temperatures
Conditions to avoid	Keep away from strong oxidizers, heat, sparks, open flame and sources of ignition. Heat, flames and sparks.

Incompatible materials This product is incompatible with alkaline metals, strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), or strong bases (e.g., lye, potassium hydroxide). Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products If exposed to extremely high temperatures, the product of thermal decomposition may include irritating vapors and carbon oxide gases (e.g., CO, CO₂)

Hazardous decomposition products None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

Skin contact May cause sensitization by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
ETHYL ACETATE	= 5620 mg/kg (Rat)	> 18000 mg/kg (Rabbit)	= 4000 ppm (Rat) 4 h
Butyl Acetate	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 0.74 mg/L (Rat) 4 h
ETHYL TRIMETHYLBENZOYL PHENYLPHOSPHINATE	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rat)	
BIS-TRIMETHYLBENZOYL PHENYLPHOSPHINE OXIDE	> 2000 mg/kg (Rat)	> 2000 mg/kg (Rat)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation. May cause skin irritation. Classification based on individual ingredients of the mixture.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation. Classification based on individual ingredients of the mixture.

Respiratory or skin sensitization May cause an allergic skin reaction. Classification based on individual ingredients of the

mixture.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

Reproductive toxicity No information available.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

12. Ecological information

Ecotoxicity The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
ETHYL ACETATE	-	LC50: 220 - 250mg/L (96h, Pimephales promelas) LC50: =484mg/L (96h, Oncorhynchus mykiss) LC50: 352 - 500mg/L (96h, Oncorhynchus mykiss)	-	EC50: =560mg/L (48h, Daphnia magna)
ISOBORNYL METHACRYLATE	-	LC50: =1.79mg/L (96h, Danio rerio)	-	-
Butyl Acetate	EC50: =674.7mg/L (72h, Desmodesmus subspicatus)	LC50: =100mg/L (96h, Lepomis macrochirus) LC50: 17 - 19mg/L (96h, Pimephales promelas)	-	-
ETHYL TRIMETHYLBENZOYL PHENYLPHOSPHINATE	-	LC50: =1.89mg/L (96h, Danio rerio)	-	-
BIS-TRIMETHYLBENZOYL PHENYLPHOSPHINE OXIDE	-	LC50: >90µg/L (96h, Danio rerio)	-	-

Persistence and Degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
ETHYL ACETATE	0.73
ISOBORNYL METHACRYLATE	5.09
Butyl Acetate	2.3
ETHYL TRIMETHYLBENZOYL PHENYLPHOSPHINATE	2.91
BIS-TRIMETHYLBENZOYL PHENYLPHOSPHINE OXIDE	5.8

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

US EPA Waste Number D001.

California waste information This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information

DOT

UN-No UN1263
Proper Shipping Name Paint
Transport hazard class(es) 3
Packing Group II
Reportable quantity - lbs ETHYL ACETATE: RQ (lb)= 5000.00
Reportable quantity lbs. (calculated) ETHYL ACETATE: RQ (lb)= 29138.00
Reportable Quantity (RQ) (RQ/% in mixture) (ETHYL ACETATE: RQ (kg)= 2270.00)
Reportable quantity kg (calculated) ETHYL ACETATE: RQ (kg)= 13228.00
Description UN1263, Paint, 3, II
Special Provisions 149, B52, IB2, T4, TP1, TP8, TP28
Emergency Response Guide Number 128

IATA

UN number or ID number UN1263
Proper Shipping Name Paint
Transport hazard class(es) 3
Packing group II
ERG Code 3L
Special Provisions A3, A72, A192
Description UN1263, Paint, 3, II

IMDG

UN number or ID number UN1263
Proper Shipping Name Paint
Transport hazard class(es) 3
Packing Group II
EmS-No F-E, S-E
Special Provisions 163
Description UN1263, Paint, 3, II, (-4°C c.c.)

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture**International Regulations**

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Complies.

Chemical name	CAS No.	U.S. Toxic Substances Control Act (TSCA) status	US TSCA inactive/active designation
Ethyl acetate 141-78-6 (<20)	141-78-6	Compliant	Active
Isobornyl Methacrylate 7534-94-3 (<20)	7534-94-3	Compliant	Active
Butyl Acetate 123-86-4 (<10)	123-86-4	Compliant	Active
Ethyl Trimethylbenzoyl Phenylphosphinate 84434-11-7 (<5)	84434-11-7		Unknown *
Bis-Trimethylbenzoyl Phenylphosphine Oxide 162881-26-7 (<1)	162881-26-7	Compliant	Active

*Contact supplier for details. One or more substances in this product are either not listed on the US TSCA inventory, listed on the confidential US TSCA inventory or are otherwise exempted from inventory listing requirements

DSL	All components are listed either on the DSL or NDSL.
EINECS/ELINCS	Contact supplier for inventory compliance status.
ENCS	Contact supplier for inventory compliance status.
IECSC	Contact supplier for inventory compliance status.
KECL	Contact supplier for inventory compliance status.
PICCS	Contact supplier for inventory compliance status.
AICS	Contact supplier for inventory compliance status.
NZIoC	Contact supplier for inventory compliance status.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Butyl Acetate	5000 lb	-	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
ETHYL ACETATE	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Butyl Acetate	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations**California Proposition 65**

This product does not require a Prop 65 chemical warning.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
ETHYL ACETATE	X	X	X
Butyl Acetate	X	X	X
BHT	X	X	X
P-HYDROXYANISOLE	X	X	X
HYDROQUINONE	X	X	X

U.S. EPA Label information**16. Other information**

NFPA	Health hazards 2	Flammability 3	Instability 0	Special hazards -
HMIS	Health hazards 2	Flammability 3	Physical hazards 0	Personal Protection X

Key or legend to abbreviations and acronyms used in the safety data sheet**Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	-	Skin designation

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
 U.S. Environmental Protection Agency ChemView Database
 European Food Safety Authority (EFSA)
 EPA (Environmental Protection Agency)
 Acute Exposure Guideline Level(s) (AELG(s))
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
 U.S. Environmental Protection Agency High Production Volume Chemicals
 Food Research Journal
 Hazardous Substance Database
 International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)
 Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
 NIOSH (National Institute for Occupational Safety and Health)
 National Library of Medicine's ChemID Plus (NLM CIP)
 National Library of Medicine's PubMed database (NLM PUBMED)
 National Toxicology Program (NTP)
 New Zealand's Chemical Classification and Information Database (CCID)
 Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
 Organization for Economic Co-operation and Development High Production Volume Chemicals Program
 Organization for Economic Co-operation and Development Screening Information Data Set
 World Health Organization

Revision Date 08-May-2025

Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

North America SDS version information - NGHS

UL release:
 GHS Revision 3
 2023 Q1

North America

Full process, including GHS and Transportation Wizards

Specific target organ toxicity (single exposure)	Category 3
Category 3 Target organ effects: Narcotic effects.	

Chemical name	RCRA - U Series Wastes	RCRA - P Series Wastes
ETHYL ACETATE	U112	-
Chemical name	California Hazardous Waste Status	
ETHYL ACETATE	Toxic Ignitable	
Butyl Acetate	Toxic	