

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS  
2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous  
Products Regulation (HPR)

Revision Date 08-May-2025

Revision Number 1

## 1. Identification

### Product identifier

**Product Name** CND SHELLAC Topcoat

### Other means of identification

**Product Code(s)** 470267, 467292, 4700637

**UN-No** UN1263

**Bulk Number** 4702670001, 4701934001, 4700637001

**Brand** CND

**Category** Nail

**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** No information available

**Restrictions on use** No information available

### Details of the supplier of the safety data sheet

#### Initial supplier identifier

Revlon Research Center

#### Supplier Address

2121 Route 27 Edison, NJ 08818

### Emergency telephone number

**Emergency Telephone Number** INFOTRAC 1-352-323-3500 (International)  
1-800-535-5053 (North America)

## 2. Hazard(s) identification

### Classification

Flammable liquids	Category 2
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3

### Label elements



**Danger****Hazard statements**

Highly flammable liquid and vapor

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

May cause drowsiness or dizziness

**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust, fume, gas, mist, vapors and spray

Contaminated work clothing must not be allowed out of the workplace

Use only outdoors or in a well-ventilated area

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground and bond container and receiving equipment

Use explosion-proof electrical, ventilating, lighting and .? equipment

Use only non-sparking tools

Take action to prevent static discharges

Wear protective gloves, eye protection and face protection

Keep cool

**Precautionary Statements - Response**

Specific treatment (see .? on this label)

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice and attention

**Skin**

If skin irritation or rash occurs: Get medical advice and attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water and then shower

Wash contaminated clothing before reuse

**Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

**Fire**In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish**Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed

Store locked up

**Precautionary Statements - Disposal**

Dispose of contents and container to an approved waste disposal plant

**Other information**

May cause long lasting harmful effects to aquatic life.

**3. Composition/information on ingredients****Substance**

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Ethyl acetate 141-78-6 ( <20 )	141-78-6	<20	-	-
Isobornyl Methacrylate 7534-94-3 ( <20 )	7534-94-3	<20	-	-
Butyl Acetate	123-86-4	<10	-	-

123-86-4 ( <10 )				
Ethyl Trimethylbenzoyl Phenylphosphinate 84434-11-7 ( <5 )	84434-11-7	<5	-	-
Bis-Trimethylbenzoyl Phenylphosphine Oxide 162881-26-7 ( <1 )	162881-26-7	<1	-	-

#### 4. First-aid measures

##### Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical attention immediately if symptoms occur.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
<b>Ingestion</b>	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

##### Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
<b>Effects of Exposure</b>	No information available.

##### Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	May cause sensitization in susceptible persons. Treat symptomatically.
---------------------------	--

#### 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b>	Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.
<b>Large Fire</b>	CAUTION: Use of water spray when fighting fire may be inefficient.
<b>Unsuitable extinguishing media</b>	Do not scatter spilled material with high pressure water streams.
<b>Specific hazards arising from the chemical</b>	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by skin contact.
<b>Explosion Data</b>	
<b>Sensitivity to mechanical impact</b>	None.
<b>Sensitivity to static discharge</b>	Yes.

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

### Methods and material for containment and cleaning up

**Methods for containment** Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

## 7. Handling and storage

### Precautions for safe handling

**Advice on safe handling** Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

## 8. Exposure controls/personal protection

### Control parameters Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
---------------	-----------	----------	-------

ETHYL ACETATE	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>
Butyl Acetate	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m <sup>3</sup> (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>

Chemical name	Alberta	British Columbia	Ontario	Quebec
ETHYL ACETATE	TWA: 400 ppm TWA: 1440 mg/m <sup>3</sup>	TWA: 150 ppm	TWA: 400 ppm	TWA: 400 ppm TWA: 1440 mg/m <sup>3</sup>
Butyl Acetate	TWA: 150 ppm TWA: 713 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>	TWA: 50 ppm STEL: 150 ppm	TWA: 50 ppm STEL: 150 ppm	TWA: 50 ppm STEL: 150 ppm

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
Ethyl acetate 141-78-6 ( <20 )	TWA: 400 ppm	TWA: 400 ppm	TWA: 400 ppm	TWA: 400 ppm
Butyl Acetate 123-86-4 ( <10 )	TWA: 50 ppm STEL: 150 ppm	TWA: 50 ppm STEL: 150 ppm	TWA: 50 ppm STEL: 150 ppm	TWA: 50 ppm STEL: 150 ppm

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
Ethyl acetate 141-78-6 ( <20 )	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup> STEL: 400 ppm STEL: 1400 mg/m <sup>3</sup>
Butyl Acetate 123-86-4 ( <10 )	TWA: 150 ppm STEL: 200 ppm	TWA: 50 ppm STEL: 150 ppm	TWA: 150 ppm STEL: 200 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>

**Appropriate engineering controls****Engineering controls**

Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Tight sealing safety goggles.

**Hand protection**

Wear suitable gloves. Impervious gloves.

**Skin and body protection**

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.  
Antistatic boots.

**Respiratory protection**

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

<b>General hygiene considerations</b>	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.
---------------------------------------	--

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Appearance</b>	Viscous
<b>Color</b>	Slightly Blue transparent
<b>Odor</b>	Mild Ester like
<b>Odor Threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>pH</b>	No data available	None known
<b>Melting / freezing point</b>	No data available	None known
<b>Boiling point / boiling range</b>	100 °C / 212.0 °F	None known
<b>Flash Point</b>	-4 °C / 24.8 °F	CC (closed cup)
<b>Evaporation Rate</b>	No data available	None known
<b>Flammability (solid, gas)</b>	No data available	No information available
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Vapor pressure</b>	No data available	None known
<b>Vapor density</b>	No data available	None known
<b>Relative density</b>	1.03-1.06	None known
<b>Water solubility</b>	Insoluble in water	None known
<b>Solubility in other solvents</b>	No data available	None known
<b>Partition coefficient: n-octanol/water</b>	No data available	None known
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>	No data available	None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	No data available	None known

### Other information

<b>Explosive properties</b>	No information available
<b>Oxidizing properties</b>	No information available
<b>Softening Point</b>	No information available
<b>Molecular Weight</b>	No information available
<b>VOC content</b>	25.65%
<b>Liquid Density</b>	No information available
<b>Bulk Density</b>	No information available

## 10. Stability and reactivity

<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under ambient conditions when stored properly (See Section 7, Storage and Handling).
<b>Possibility of hazardous reactions</b>	None under normal processing.
<b>Hazardous Polymerization</b>	May occur, if exposed to extremely high temperatures
<b>Conditions to avoid</b>	Keep away from strong oxidizers, heat, sparks, open flame and sources of ignition. Heat, flames and sparks.

**Incompatible materials** This product is incompatible with alkaline metals, strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), or strong bases (e.g., lye, potassium hydroxide). Strong acids. Strong bases. Strong oxidizing agents.

**Hazardous decomposition products** If exposed to extremely high temperatures, the product of thermal decomposition may include irritating vapors and carbon oxide gases (e.g., CO, CO<sub>2</sub>)

**Hazardous decomposition products** None known based on information supplied.

## 11. Toxicological information

### Information on likely routes of exposure

#### Product Information

**Inhalation** Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

**Eye contact** Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

**Skin contact** May cause sensitization by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes skin irritation.

**Ingestion** Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

### Acute toxicity

### Numerical measures of toxicity

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
ETHYL ACETATE	= 5620 mg/kg ( Rat )	> 18000 mg/kg ( Rabbit )	= 4000 ppm ( Rat ) 4 h
Butyl Acetate	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 0.74 mg/L ( Rat ) 4 h
ETHYL TRIMETHYLBENZOYL PHENYLPHOSPHINATE	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	
BIS-TRIMETHYLBENZOYL PHENYLPHOSPHINE OXIDE	> 2000 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes skin irritation. May cause skin irritation. Classification based on individual ingredients of the mixture.

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes serious eye irritation. Classification based on individual ingredients of the mixture.

**Respiratory or skin sensitization** May cause an allergic skin reaction. Classification based on individual ingredients of the

mixture.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** No information available.

**Reproductive toxicity** No information available.

**STOT - single exposure** May cause drowsiness or dizziness.

**STOT - repeated exposure** No information available.

**Aspiration hazard** No information available.

## 12. Ecological information

**Ecotoxicity** The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
ETHYL ACETATE	-	LC50: 220 - 250mg/L (96h, Pimephales promelas) LC50: =484mg/L (96h, Oncorhynchus mykiss) LC50: 352 - 500mg/L (96h, Oncorhynchus mykiss)	-	EC50: =560mg/L (48h, Daphnia magna)
ISOBORNYL METHACRYLATE	-	LC50: =1.79mg/L (96h, Danio rerio)	-	-
Butyl Acetate	EC50: =674.7mg/L (72h, Desmodesmus subspicatus)	LC50: =100mg/L (96h, Lepomis macrochirus) LC50: 17 - 19mg/L (96h, Pimephales promelas)	-	-
ETHYL TRIMETHYLBENZOYL PHENYLPHOSPHINATE	-	LC50: =1.89mg/L (96h, Danio rerio)	-	-
BIS-TRIMETHYLBENZOYL PHENYLPHOSPHINE OXIDE	-	LC50: >90µg/L (96h, Danio rerio)	-	-

**Persistence and Degradability** No information available.

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
ETHYL ACETATE	0.73
ISOBORNYL METHACRYLATE	5.09
Butyl Acetate	2.3
ETHYL TRIMETHYLBENZOYL PHENYLPHOSPHINATE	2.91
BIS-TRIMETHYLBENZOYL PHENYLPHOSPHINE OXIDE	5.8



Other adverse effects No information available.

### 13. Disposal considerations

#### Waste treatment methods

**Waste from residues/unused products** Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

**US EPA Waste Number** D001.

**California waste information** This product contains one or more substances that are listed with the State of California as a hazardous waste.

### 14. Transport information

#### DOT

**UN-No** UN1263

**Proper Shipping Name** Paint

**Transport hazard class(es)** 3

**Packing Group** II

**Reportable quantity - lbs** ETHYL ACETATE: RQ (lb)= 5000.00

**Reportable quantity lbs. (calculated)** ETHYL ACETATE: RQ (lb)= 29138.00

**Reportable Quantity (RQ) (RQ/% in mixture)** (ETHYL ACETATE: RQ (kg)= 2270.00)

**Reportable quantity kg (calculated)** ETHYL ACETATE: RQ (kg)= 13228.00

**Description** UN1263, Paint, 3, II

**Special Provisions** 149, B52, IB2, T4, TP1, TP8, TP28

**Emergency Response Guide Number** 128

#### IATA

**UN number or ID number** UN1263

**Proper Shipping Name** Paint

**Transport hazard class(es)** 3

**Packing group** II

**ERG Code** 3L

**Special Provisions** A3, A72, A192

**Description** UN1263, Paint, 3, II

#### IMDG

**UN number or ID number** UN1263

**Proper Shipping Name** Paint

**Transport hazard class(es)** 3

**Packing Group** II

**EmS-No** F-E, S-E

**Special Provisions** 163

**Description** UN1263, Paint, 3, II, (-4°C c.c.)

### 15. Regulatory information

**Safety, health and environmental regulations/legislation specific for the substance or mixture****International Regulations**

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

**International Inventories**

**TSCA** Complies.

Chemical name	CAS No.	U.S. Toxic Substances Control Act (TSCA) status	US TSCA inactive/active designation
Ethyl acetate 141-78-6 ( <20 )	141-78-6	Compliant	Active
Isobornyl Methacrylate 7534-94-3 ( <20 )	7534-94-3	Compliant	Active
Butyl Acetate 123-86-4 ( <10 )	123-86-4	Compliant	Active
Ethyl Trimethylbenzoyl Phenylphosphinate 84434-11-7 ( <5 )	84434-11-7		Unknown *
Bis-Trimethylbenzoyl Phenylphosphine Oxide 162881-26-7 ( <1 )	162881-26-7	Compliant	Active

\*Contact supplier for details. One or more substances in this product are either not listed on the US TSCA inventory, listed on the confidential US TSCA inventory or are otherwise exempted from inventory listing requirements

<b>DSL</b>	All components are listed either on the DSL or NDSL.
<b>EINECS/ELINCS</b>	Contact supplier for inventory compliance status.
<b>ENCS</b>	Contact supplier for inventory compliance status.
<b>IECSC</b>	Contact supplier for inventory compliance status.
<b>KECL</b>	Contact supplier for inventory compliance status.
<b>PICCS</b>	Contact supplier for inventory compliance status.
<b>AICS</b>	Contact supplier for inventory compliance status.
<b>NZIoC</b>	Contact supplier for inventory compliance status.

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Butyl Acetate	5000 lb	-	-	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
ETHYL ACETATE	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Butyl Acetate	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

**US State Regulations****California Proposition 65**

This product does not require a Prop 65 chemical warning.

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
ETHYL ACETATE	X	X	X
Butyl Acetate	X	X	X
BHT	X	X	X
P-HYDROXYANISOLE	X	X	X
HYDROQUINONE	X	X	X

**U.S. EPA Label information****16. Other information**

<b>NFPA</b>	<b>Health hazards</b> 2	<b>Flammability</b> 3	<b>Instability</b> 0	<b>Special hazards</b> -
<b>HMIS</b>	<b>Health hazards</b> 2	<b>Flammability</b> 3	<b>Physical hazards</b> 0	<b>Personal Protection</b> X

**Key or legend to abbreviations and acronyms used in the safety data sheet****Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	-	Skin designation

**Key literature references and sources for data used to compile the SDS**

Agency for Toxic Substances and Disease Registry (ATSDR)  
 U.S. Environmental Protection Agency ChemView Database  
 European Food Safety Authority (EFSA)  
 EPA (Environmental Protection Agency)  
 Acute Exposure Guideline Level(s) (AELG(s))  
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act  
 U.S. Environmental Protection Agency High Production Volume Chemicals  
 Food Research Journal  
 Hazardous Substance Database  
 International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)  
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)  
NIOSH (National Institute for Occupational Safety and Health)  
National Library of Medicine's ChemID Plus (NLM CIP)  
National Library of Medicine's PubMed database (NLM PUBMED)  
National Toxicology Program (NTP)  
New Zealand's Chemical Classification and Information Database (CCID)  
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications  
Organization for Economic Co-operation and Development High Production Volume Chemicals Program  
Organization for Economic Co-operation and Development Screening Information Data Set  
World Health Organization

**Revision Date** 08-May-2025

**Revision Note** No information available.

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**North America SDS version information - NGHS**

UL release:  
GHS Revision 3  
2023 Q1

**North America**

Full process, including GHS and Transportation Wizards

Specific target organ toxicity (single exposure)	Category 3
Category 3 Target organ effects: Narcotic effects.	

Chemical name	RCRA - U Series Wastes	RCRA - P Series Wastes
ETHYL ACETATE	U112	-
Chemical name	California Hazardous Waste Status	
ETHYL ACETATE	Toxic Ignitable	
Butyl Acetate	Toxic	